

EXHIBIT C

PATENT APPLICATION

09080774

INITIALS

CONTENTS

	Date received (Incl. C. of M.) or Date Mailed		Date received (Incl. C. of M.) or Date Mailed
1. Application 9 Drawing papers.		42.	
2. Fee Authorization	5-18-98	43.	
3. FDS	9-28-98	44.	
4. Rev. of PA	5-20-99	45.	
5. Notice of Allowance	7-25-99	46.	
6. Election Rep (1 month)	8-1-99	47.	
7. E. of time (2)	11/8/99	48.	
8. election	11/8/99	49.	
9. Rejection (3 months)	12/13/99	50.	
10. Amendment / Drawings	3-20-00	51.	
11. Office Action / Exam. Rept. B	04-10-00	52.	
12. FR	1-10-00	53.	
13. Final Decision 9-23-00	5-23-00	54.	
14.		55.	
15.		56.	
16.		57.	
17.		58.	
18.		59.	
19.		60.	
20.		61.	
21.		62.	
22.		63.	
23.		64.	
24.		65.	
25.		66.	
26.		67.	
27.		68.	
28.		69.	
29.		70.	
30.		71.	
31.		72.	
32.		73.	
33.		74.	
34.		75.	
35.		76.	
36.		77.	
37.		78.	
38.		79.	
39.		80.	
40.		81.	
41.		82.	

(FRONT)

FCS0000336

09/080714
05/10/96

327	172	Subclass	ISSUE CLASSIFICATION
-----	-----	----------	----------------------

PATENT NUMBER
6107851

U.S. UTILITY PATENT APPLICATION

O.I.P.E. PATENT DATE
SCANNED *MIC* *at Du* AUG 22 2000

SECTOR	CLASS 327	SUBCLASS 172	ART UNIT 2816	EXAMINER Zweizig
--------	---------------------	------------------------	-------------------------	----------------------------

FILED WITH: ☐ DISK (CRF) ☐ FICHE
(Attached to patent on right inside flap)

PREPARED AND APPROVED FOR ISSUE

ISSUING CLASSIFICATION

ORIGINAL		CROSS REFERENCE(S)	
CLASS	SUBCLASS	CLASS	SUBCLASS (ONE SUBCLASS PER BLOCK)
327	172	327	531 544

INTERNATIONAL CLASSIFICATION

H03K	3/017
-------------	--------------

☐ Continued on issue flap inside File Jacket

<input type="checkbox"/> TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drawn 9	Figs. Drawn 9	Print Figs. 3	Total Claims 18	Print Claim for O.G. 1
<input type="checkbox"/> a) The term of this patent subsequent to _____ (date) has been disclaimed.	(Assistant Examiner) _____ (Date) _____			NOTICE OF ALLOWANCE MAILED	
<input type="checkbox"/> b) The term of this patent shall not extend beyond the expiration date of U.S. Patent No. _____	Jeffrey Zweizig Primary Examiner 2816 <i>Jeffrey Zweizig</i> 4/6/00 (Primary Examiner) (Date)			ISSUE FEE	
				Amount Due 11210.00	Date Paid 5-30-00
<input type="checkbox"/> c) The terminal _____ months of this patent have been disclaimed.	<i>Soriano</i> 4/13/00 (Legal Instruments Examiner) (Date)			ISSUE BATCH NUMBER 183	

WARNING:
The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-438A
(Rev. 10/97)

ISSUED TO FILE

(LABEL AREA)

(FACE)

FCS0000337

PART B—ISSUE FEE TRANSMITTAL

Complete and mail this form, together with app. fee, to: **Box ISSUE FEE
Assistant Commissioner for Patents
Washington, D.C. 20231**

MAY 30 2000

MAILING INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE. Blocks 1 through 4 should be completed where appropriate. All correspondence (including the Issue Fee Receipt, the Patent, advance orders and notification of maintenance fees) will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (note: Legibly mark-up with any corrections or use Block 9)

MMC2/0410

**BRADLEY J. BEREZNAK, ESQ.,
BLAKELEY, SOKOLOFF, TAYLOR, ZAFMAN LLP
12400 WILSHIRE BOULEVARD
SEVENTH FLOOR
LOS ANGELES CA 90025**

Note: The certificate of mailing below can only be used for domestic mailings of the Issue Fee Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing.

Certificate of Mailing

I hereby certify that this Issue Fee Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Box Issue Fee address above on the date indicated below.

David Y. Bulten (Depositor's name)
David Y. Bulten (Signature)
May 26, 2000 (Date)

APPLICATION NO.	FILING DATE	TOTAL CLAIMS	EXAMINER AND GROUP ART UNIT	DATE MAILED
09/080,774	05/18/98	018	ZWEIZIG, J	2816 04/10/00

First Named Applicant: **BALAKRISHNAN,** 35 USC 154(b) term ext. = 0 Days.

TITLE OF INVENTION: OFFLINE CONVERTER WITH INTEGRATED SOFTSTART AND FREQUENCY JITTER

ATTY'S SOCKET NO.	CLASS-SUBCLASS	BATCH NO.	APPL. TYPE	SMALL ENTITY	FEE DUE	DATE DUE
2	233/248	327-172.000	K83	UTILITY	NO	\$1210.00 07/10/00

1. Change of correspondence address or indication of "Fee Address" (PT CFI 1.582). Use of PTO form(s) and Outgoing Number are recommended, but not required.

☐ Change of correspondence address (for Change of Correspondence Address form PTO/SB/128) attached.

☐ "Fee Address" indication (for "Fee Address" indication form PTO/SB/47) attached.

2. For printing on the patent front page, list (1) the names of up to 3 registered patent attorneys or agents OR, alternatively, (2) the names of a single firm (filing as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

**BLAKELEY, SOKOLOFF,
TAYLOR & ZAFMAN, LLP**

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. Inclusion of assignee data is only appropriate when an assignment has been previously submitted to the PTO or is being submitted under separate cover. Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE: **POWER INTEGRATIONS, INC.**

(B) RESIDENCE (CITY & STATE OR COUNTRY): **Sunnyvale, California**

Please check the appropriate assignee category indicated below (will not be printed on the patent):

☐ Individual ☒ Corporation or other private group entity ☐ government

4a. The following fees are enclosed (note: check payable to Commissioner of Patents and Trademarks):

☒ Issue Fee

☒ Advance Order - # of Copies: **5**

4b. The following fees or deficiency in these fees should be charged to:

DEPOSIT ACCOUNT NUMBER: **02-2666**

(ENCLOSE AN EXTRA COPY OF THIS FORM)

☐ Issue Fee

☐ Advance Order - # of Copies: **5**

The COMMISSIONER OF PATENTS AND TRADEMARKS is requested to apply the Issue Fee to the application identified above.

(Authorized Signature) *Bradley J. Berezna* Date: **5/26/00**

Bradley J. Berezna, Esq. PER. NO. 33,474

NOTE: The Issue Fee will not be accepted from anyone other than the applicant, a registered attorney or agent, or the assignee or other party in interest as shown by the records of the Patent and Trademark Office.

Burdan Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending on the needs of the individual case. Any comments on the amount of time required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND FEES AND THIS FORM TO: Box Issue Fee, Assistant Commissioner for Patents, Washington D.C. 20231

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMIT THIS FORM WITH FEE

PTOL-838 (REV. 10-99) Approved for use through 06/30/00. OMB 0851-0033

Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

05/21/2000 TTR838 00000174 09580774 1210.00 15.48

01 TC142 02 TC151

FCS0000338

Due date	Client Name	1F09-080774
5/10/2000	Power Integrations, Inc.	
Decker Initial	3692 . P036	
Deck. Sup. Initial	BJB JYG	
Atty Initial		
Pat/Sec/Reg	080,774	
Description		
Issue fee due		
7/10/2000		
Formal drawings required by 7/10/2000		
7/3/2000		

Due date	Client Name	1F09-080774
4/10/2000	Power Integrations, Inc.	
Decker Initial	3692 . P036	
Deck. Sup. Initial	BJB JYG	
Atty Initial		
Pat/Sec/Reg	080,774	
Description		
Formal drawings required by 7/10/2000		
7/3/2000		

Due date	Client Name	1F09-080774
7/10/2000	Power Integrations, Inc.	
Decker Initial	3692 . P036	
Deck. Sup. Initial	BJB JYG	
Atty Initial		
Pat/Sec/Reg	080,774	
Description		
Formal drawings required		
7/3/2000		

PART B - ISSUE FEE TRANSMITTAL

Complete and mail this form, together with appropriate fee, to: **Box ISSUE FEE
Assistant Commissioner for Patents
Washington, D.C. 20231**

MAILING INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE. Blocks 1 through 4 should be completed where appropriate. **ISSUE FEE** correspondence including the Issue Fee Receipt, the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Lightly mark up with any additions or use Block 1)

MNC2/0410

**BRADLEY J. BEREZNAK, ESQ.
BLAKELEY, SOKOLOFF, TAYLOR, ZAFMAN LLP
12400 WILSHIRE BOULEVARD
SEVENTH FLOOR
LOS ANGELES CA 90025**

Note: The certificate of mailing below can only be used for domestic mailings of the Issue Fee Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing.

Certificate of Mailing

I hereby certify that this Issue Fee Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Box Issue Fee address above on the date indicated below.

Patentee's name Patentee Y. Balligan
Signature [Signature]
Date May 26, 2000

APPLICATION NO.	FILING DATE	TOTAL CLAIMS	EXAMINER AND GROUP ART UNIT	DATE MAILED
09/080,774	05/18/98	018	ZWEIZIG, J	2816 04/10/00

First Named Applicant **BALAKRISHNAN,** **35 USC 154(b) term ext. = 0 Days.**

TITLE OF INVENTION **OFFLINE CONVERTER WITH INTEGRATED SOFTSTART AND FREQUENCY JITTER**

ATTY'S DOCKET NO.	CLASS-SUBCLASS	BATCH NO.	APPL. TYPE	SMALL ENTITY	FEE DUE	DATE DUE
2 233/248	327-172.000	K83	UTILITY	NO	\$1210.00	07/10/00

1. Change of correspondence address or indication of "Fee Address" (PTO Form 1.262). Use of PTO form(s) and Customer Number are recommended, but not required.

☐ Change of correspondence address (for Change of Correspondence Address form PTO/SB/102) attached.

☐ "Fee Address" indication (for "Fee Address" indication form PTO/SB/107) attached.

2. For printing on the patent front page, list: (1) the names of up to 3 registered patent attorneys or agents OR, alternatively, (2) the name of a single firm (acting as a member a registered attorney or agent) and the names of up to 3 registered patent attorneys or agents. If no names is listed, no names will be printed.

**BLAKELY, SOKOLOFF,
TAYLOR & ZAFMAN, LLP**

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)
PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. Inclusion of assignee data is only appropriate when an assignment has been previously submitted to the PTO or is being submitted under separate cover. Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE: POWER INTEGRATIONS, INC.

(B) RESIDENCE (CITY A STATE OR COUNTRY)
Sunnyvale, California

Please check the appropriate assignee category indicated below (will not be printed on the patent)

☐ Individual ☐ Corporation or other private group entity ☐ government

4a. The following fees are enclosed (make check payable to Commissioner of Patents and Trademarks):

☒ Issue Fee
☒ Advance Order - # of Copies 5

4b. The following fees or deficiency in these fees should be charged to:
DEPOSIT ACCOUNT NUMBER 02-2666
(ENCLOSE AN EXTRA COPY OF THIS FORM)

☐ Issue Fee
☐ Advance Order - # of Copies

The COMMISSIONER OF PATENTS AND TRADEMARKS is requested to apply the Issue Fee to the application identified above.

(Authorized Signature) Bradley J. Bereznek, Esq. **Date** 5/26/00

NOTE: The Issue Fee will not be accepted from anyone other than the applicant, a registered attorney or agent, or the assignee or other party in interest as shown by the records of the Patent and Trademark Office.

Service Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending on the needs of the individual case. Any comments on the amount of time required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, D.C. 20231. **DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND FEES AND THIS FORM TO: Box Issue Fee, Assistant Commissioner for Patents, Washington D.C. 20231**

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMIT THIS FORM WITH FEE

*TOL-658 (REV.10-98) Approved for use through 06/30/99. OMB 0651-0033

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

FCS0000340

PATENT APPLICATION FEE DETERMINATION RECORD Effective October 1, 1997					Application or Docket Number	
CLAIMS AS FILED - PART I						
(Column 1)		(Column 2)		SMALL ENTITY TYPE <input type="checkbox"/>		OR
FOR	NUMBER FILED	NUMBER EXTRA		RATE	FEE	OTHER THAN SMALL ENTITY
BASIC FEE					395.00	OR
TOTAL CLAIMS	37	minus 20 =	17	x\$11=		OR
INDEPENDENT CLAIMS	4	minus 3 =	1	x\$22=		OR
MULTIPLE DEPENDENT CLAIM PRESENT				x\$41=		OR
				+135=		OR
				TOTAL		OR
				TOTAL		OR
CLAIMS AS AMENDED - PART II						
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY
AMENDMENT A	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE	ADDITIONAL FEE	OR
Total	36	Minus	37	x\$11=		OR
Independent	4	Minus	4	x\$22=		OR
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM				x\$41=		OR
				+135=		OR
				TOTAL		OR
				TOTAL		OR
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY
AMENDMENT B	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE	ADDITIONAL FEE	OR
Total	0	Minus	0	x\$11=		OR
Independent	0	Minus	0	x\$22=		OR
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM				x\$41=		OR
				+135=		OR
				TOTAL		OR
				TOTAL		OR
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY
AMENDMENT C	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE	ADDITIONAL FEE	OR
Total	0	Minus	0	x\$11=		OR
Independent	0	Minus	0	x\$22=		OR
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM				x\$41=		OR
				+135=		OR
				TOTAL		OR
				TOTAL		OR

* If the difference in column 1 is less than zero, enter "0" in column 2.

* If the entry in column 1 is less than the entry in column 2, enter "0" in column 3.


** If the "Highest Number Previously Paid For" in THIS SPACE is less than 20, enter "20."

*** If the "Highest Number Previously Paid For" in THIS SPACE is less than 3, enter "3."

The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.

FORM PTO-575 (Rev. 8/97) U.S. Government Printing Office: 1997 - 435-575/0104 Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

FCS0000341

SEARCHED				SEARCH NOTES (INCLUDING SEARCH STRATEGY)	
Class	Sub.	Date	Exmr.		
327	172 173 174 175 176 530 531 544	12/13/60	JZ		
Update	above	4/6/60			

INTERFERENCE SEARCHED			
Class	Sub.	Date	Exmr.
327	172 531 544	4/6/60	JZ

[REDACTED]

FCS0000342

ISSUE SLIP STAPLE AREA (for additional cross references)

POSITION	INITIALS	ID NO.	DATE
FEE DETERMINATION		70803	
O.L.P.E. CLASSIFIER		71477	5/26/96
FORMALITY REVIEW	KNO.		6/3/98

INDEX OF CLAIMS

✓ _____ Rejected
 = _____ Allowed
 - (Through numeral) Canceled
 + _____ Restricted
 N _____ Non-elected
 I _____ Interference
 A _____ Appeal
 O _____ Objected

Claim	Date	Claim	Date	Claim	Date
1		51		101	
2		52		102	
3		53		103	
4		54		104	
5		55		105	
6		56		106	
7		57		107	
8		58		108	
9		59		109	
10		60		110	
11		61		111	
12		62		112	
13		63		113	
14		64		114	
15		65		115	
16		66		116	
17		67		117	
18		68		118	
19		69		119	
20		70		120	
21		71		121	
22		72		122	
23		73		123	
24		74		124	
25		75		125	
26		76		126	
27		77		127	
28		78		128	
29		79		129	
30		80		130	
31		81		131	
32		82		132	
33		83		133	
34		84		134	
35		85		135	
36		86		136	
37		87		137	
38		88		138	
39		89		139	
40		90		140	
41		91		141	
42		92		142	
43		93		143	
44		94		144	
45		95		145	
46		96		146	
47		97		147	
48		98		148	
49		99		149	
50		100		150	

If more than 150 claims or 10 actions
staple additional sheet here

(LEFT INSIDE)

FCS0000343

1

FCS0000344

PATENT APPLICATION SERIAL NO. 09/080774

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

03/22/1994 HUNTER 0000046 122075 09080774
02 FC101 750.00 DP
03 FC102 82.00 DP
04 FC103 2.00 CH 372.00 DP

PTO-1556
(5/87)

FCS0000345

SERIAL NUMBER 09/080,774	FILED DATE 05/18/98	CLASS 327	GROUP ART UNIT 2816	ATTORNEY DOCKET NO. 233/248		
APPLICANT BALU BALAKIRSHNAN, SARATOGA, CA; ALEX DJENGUERIAN, SARATOGA, CA; LEIF LUND, SAN JOSE, CA.						
CONTINUING DOMESTIC DATA*** VERIFIED <u>none</u> <u>JZ</u>						
371 (NAT'L STAGE) DATA*** VERIFIED <u>none</u> <u>JZ</u>						
FOREIGN APPLICATIONS*** VERIFIED <u>none</u> <u>JZ</u>						
FOREIGN FILING LICENSE GRANTED 06/03/98						
Foreign Priority claimed 35 USC 119 is-4 conditions met <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Verified and Acknowledged <u>JZ</u>		<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Met after Allowance	STATE OR COUNTRY CA	SHEETS DRAWING 9	TOTAL CLAIMS 37	INDEPENDENT CLAIMS 4
ADDRESS LYON & LYON FIRST INTERSTATE WORLD CENTER 633 W FIFTH STREET 47TH FLOOR LOS ANGELES CA 90071						
TITLE OFFLINE CONVERTER WITH INTEGRATED SOFTSTART AND FREQUENCY JITTER						
FILING FEE RECEIVED \$1,246	FEES: Authority has been given in Paper No. _____ to charge/credit DEPOSIT ACCOUNT No. _____ for the following:			<input type="checkbox"/> All Fees <input type="checkbox"/> 1.16 Fees (Filing) <input type="checkbox"/> 1.17 Fees (Processing Ext. of time) <input type="checkbox"/> 1.18 Fees (Issue) <input type="checkbox"/> Other _____ <input type="checkbox"/> Credit _____		

FCS0000346



Bib Data Sheet



UNITED STATES DEPARTMENT OF COMMERCE
 Patent and Trademark Office
 Address: COMMISSIONER OF PATENTS AND TRADEMARKS
 Washington, D.C. 20530

SERIAL NUMBER 09/080,774	FILING DATE 05/18/1998 RULE	CLASS 327	GROUP ART UNIT 2816	ATTORNEY DOCKET NO. 233/248
APPLICANTS BALU BALAKRISHNAN, SARATOGA, CA; ALEX DJENGUERIAN, SARATOGA, CA; LEIF LUND, SAN JOSE, CA;				
** CONTINUING DATA **				
** FOREIGN APPLICATIONS **				
IF REQUIRED, FOREIGN FILING LICENSE GRANTED ** 06/03/1998				
Foreign Priority claimed <input type="checkbox"/> yes <input type="checkbox"/> no 35 USC 119 (a-d) conditions met <input type="checkbox"/> yes <input type="checkbox"/> no <input type="checkbox"/> Met after Allowance		STATE OR COUNTRY CA	SHEETS DRAWING 9	TOTAL CLAIMS 37
Verified and Acknowledged Examiner's Signature _____ Initials _____				INDEPENDENT CLAIMS 4
ADDRESS BRADLEY J. BEREZNAK, ESQ. BLAKELEY, SOKOLOFF, TAYLOR, ZAFMAN LLP. 12400 WILSHIRE BOULEVARD SEVENTH FLOOR LOS ANGELES, CA 90025				
TITLE OFFLINE CONVERTER WITH INTEGRATED SOFTSTART AND FREQUENCY JITTER				
FILING FEE RECEIVED 1248	FEES: Authority has been given in Paper No. _____ to charge/credit DEPOSIT ACCOUNT No. _____ for following:		<input type="checkbox"/> All Fees <input type="checkbox"/> 1.16 Fees (Filing) <input type="checkbox"/> 1.17 Fees (Processing Ext. of time) <input type="checkbox"/> 1.18 Fees (Issue) <input type="checkbox"/> Other _____ <input type="checkbox"/> Credit	

1 of 1

4/13/00 11:38 AM

FCS0000347

233/248
PATENT

SPECIFICATION

TITLE OF THE INVENTION

OFFLINE CONVERTER WITH INTEGRATED SOFTSTART AND FREQUENCY JITTER

5

BACKGROUND

Field Of The Invention

The field of the present invention pertains to the field of power supplies and among other things to the regulation of power supplies.

Background Of The Invention

Power supplies that convert an AC mains voltage to a DC voltage for use by integrated electronic devices, amongst other devices, are known. The power supplies are required to maintain the output voltage, current or power within a regulated range for efficient and safe operation of the electronic device. Switches that operate according a pulse width modulated control to maintain the output voltage, current, or power of the power supply within a regulated range are also known. These switches utilize an oscillator and related circuitry to vary the switching frequency of operation of the switch, and therefore regulated the power, current or voltage that is supplied by the power supply.

20

A problem with utilizing pulse width modulated switches is that they operate at a relatively high frequency compared to the frequency of the AC mains voltage, which results in a high frequency signal being generated by the power supply. This high frequency signal is injected back into the AC mains input and becomes a component of the AC mains signal. The

09880774-051808

1 2

Express Mail No. BM563810388US
Docket No. 233/248
May 18, 1996

FCS0000348

233/248
PATENT

high frequency signals are also radiated by the power supply as electromagnetic waves. These high frequency signals add to the Electromagnetic Interference (EMI) of the power supply, and in fact are the largest contributors to the EMI of the power supply. The EMI generated by the power supply can cause problems for communications devices in the vicinity of the power supply and the high frequency signal which becomes a component of the AC mains signal will be provided to other devices in the power grid which also causes noise problems for those devices. Further, the radiated EMI by the power supply can interfere with radio and television transmissions that are transmitted over the air by various entities.

To combat the problem of EMI, several specifications have been developed by the Federal Communications Commission (FCC) in the United States and the European Community (EC) have established specification that specify the maximum amount of EMI that can be produced by classes of electronic devices. Since power supplies generate a major component of the EMI for electronic devices, an important step in designing a power supply is minimizing the EMI provided by the power supply to levels with the acceptable limits of the various standards. Since, a power supply can be utilized in many different countries of the world, the EMI produced should be within the most stringent limits worldwide to allow for maximum utilization of the power supply.

A known way of minimizing the EMI provided by the power supply is by adding an EMI filter to the input of the power supply. An EMI filter generally utilizes at least one inductor, capacitor and resistor in combination. However, the greater EMI produced by the power supply the larger the components that are utilized as part of the EMI filter. The cost of the EMI filter is in large part determined by the size of the inductor and capacitor utilized. The longer the

Express Mail No. EM543810380/S
Docket No: 233/248
May 18, 1998

FCS0000349

233/248
PATENT

components, the higher the cost of the power supply. Further, simply utilizing an EMI filter does not address the radiated EMI.

Another problem associated with pulse width modulated switches results from operation of the power supply at start up. At start up, the voltage, current and power at the output of the power supply will essentially be zero. The pulse width modulated switch will then conduct for the maximum possible amount of time in each cycle of operation. The result of this is a maximum inrush current into the power supply. The maximum inrush current is greater than the current that is utilized during normal operation of the power supply. The maximum inrush current stresses the components of power supply and switch. Stress is specifically a problem for the switch, or transistor, the transformer of the power supply, and the secondary side components of the power supply. The stress caused by the maximum inrush current decreases the overall life of the power supply and increases the cost of the power supply because the maximum rating of the components used in the power supply to not destruct from the inrush currents will be greater than the maximum rating required for normal operation.

Further, when the pulse width modulated switch conducts for the maximum possible amount of time in each cycle of operation the voltage, current and power at the output of the power supply rise rapidly. Since the feedback circuit of the power supply often does not respond as fast as the operating frequency of the switch, the rapid rise of the voltage, current and power will often result in an overshoot of the maximum voltage in the regulation range which will cause damage to the device being supplied power by the power supply.

Referring to Fig. 1 a known power supply that attempts to minimize EMI and reduce startup stress is depicted. A rectifier 10 rectifies the filtered AC mains voltage 5, from EMI filter 120, input by the AC mains to generate a rectified voltage 15. Power supply capacitor 20 then

233/248
PATENT

generates a substantially DC voltage with a ripple component. The rectified voltage 15 with ripple component is provided to the primary winding 35 of transformer 40 that is used to provide power to secondary winding 45. The output of secondary winding 45 is provided to secondary rectifier 50 and secondary capacitor 55 that provide a secondary DC voltage 60 at the power supply output 65 to the device that is coupled to the power supply.

In order to maintain the secondary DC voltage within a regulate range a feedback loop including an optocoupler 70, zener diode 75 and a feedback resistor 80 provides a signal indicative of the voltage at the power supply output 65 to feedback pin 85 of pulse width modulated switch 90. The voltage magnitude at the feedback terminal is utilized to vary the duty cycle of a switch coupled between the drain terminal 95 and common terminal 100 of the pulse width modulated switch 90. By varying the duty cycle of the switch the average current flowing through the primary winding and therefore the energy stored by the transformer 40 which in turn controls the power supplied to the power supply output 65 is kept within the regulated range. A compensation circuit 105 is coupled to the feedback pin 85 in order to lower the bandwidth of the frequency of operation of the pulse width modulator.

Inrush currents are minimized at start up by use of soft start capacitor 110. Soft start functionality is termed to be a functionality that reduces the inrush currents at start up. At this instant a current begins to flow through feedback resistor 80 and thereby into soft start capacitor 110. As the voltage of soft start capacitor 110 increases slowly, current will flow through light emitting diode 115 of optocoupler 70 thereby controlling the duty cycle of the switch. Once the voltage of the soft start capacitor 110 reaches the reverse breakdown voltage of zener diode 75 current will flow through zener diode 75. The approach described above will reduce the inrush currents into the power supply, however, it will be several cycles before the light emitting diode

4 5

Express Mail No. EM563810388US
Docket No. 233248
May 11, 1996

FCS0000351

233/248
PATENT

115 will begin conducting. During the several cycles the maximum inrush current will still flow through the primary winding and other secondary side components. During these cycles the transformer may saturate, and therefore the transformer may have to be designed utilizing a higher core size than would be required for normal operation even with the use of soft start capacitor as in Fig. 1.

To reduce the EMI output by the power supply an EMI filter 120 is utilized.

Additionally, pulse width modulated switch 90 is equipped with frequency oscillation terminals 125 and 130. Frequency oscillation terminal 125 and 130 receive a jitter current 135 that varies according to the ripple component of substantially DC voltage 25. The jitter current 135 is used to vary the frequency of the saw-toothed waveform generated by the oscillator contained in the pulse width modulated switch 90. The saw toothed waveform generated by the oscillator is compared to the feedback provided at the feedback pin 85. As the frequency of the saw toothed waveform varies, so will the switching frequency of the switch coupled between the drain and common terminal. This allows the switching frequency of the switch to be spread over a larger bandwidth, which minimizes the peak value of the EMI generated by the power supply at each frequency. By reducing the EMI the ability to comply with government standards is increased, because the government standards specify quasi-peak and average values at given frequency levels. Varying the frequency of operation of the pulse width modulated switch by varying the oscillation frequency of the oscillator is referred to as frequency jitter.

A problem associated with the EMI reduction scheme described with respect to Fig. 1 is that the ripple component will have variances due to variations in the line voltage and output load. Additionally, since the ripple may vary, design and the component value of EMI resistor

Express Mail No. EM4563810388US
Docket No: 233/248
May 18, 1998

FCS0000352

233/248
PATENT

140 is difficult to determine and correspondingly design of the power supply becomes problematic.

SUMMARY OF THE INVENTION

5 In one embodiment the present invention comprises a pulse width modulated switch comprising a switch that allows a signal to be transmitted between a first terminal and a second terminal according to a drive signal. The pulse width modulated switch also comprises a frequency variation circuit that provides a frequency variation signal and an oscillator that provides an oscillation signal having a frequency that varies within a frequency range according to the frequency variation signal. The oscillator further provides a maximum duty cycle signal comprising a first state and a second state. The pulse width modulated circuit further comprises a drive circuit that provides the drive signal when the maximum duty cycle signal is in the first state and a magnitude of the oscillation signal is below a variable threshold level.

Another embodiment of the present invention comprises a pulse width modulated switch comprising a switch comprising a control input, the switch allowing a signal to be transmitted between a first terminal and a second terminal according to a drive signal. The pulse width modulated switch also comprises an oscillator that provides a maximum duty cycle signal comprising an on-state and an off-state, a drive circuit that provides the drive signal, and a soft start circuit that provides a signal instructing said drive circuit to disable the drive signal during
20 at least a portion of said on-state of the maximum duty cycle.

In an alternate embodiment the present invention comprises a regulation circuit comprising a switch that allows a signal to be transmitted between a first terminal and a second

6 7

Express Mail No. EM563810348US
Docket No: 233/248
May 12, 1998

FCS0000353

233/248
PATENT

terminal according to a drive signal, a drive circuit that provides the drive signal and a soft start circuit that provides a signal instructing the drive circuit to disable the drive signal.

5 In yet another embodiment the present invention comprises a regulation circuit comprising a switch that allows a signal to be transmitted between a first terminal and a second terminal according to a drive signal, a frequency variation circuit that provides a frequency variation signal, and a drive circuit that provides a drive signal for a maximum time period of a time duration cycle. The time duration of the cycle varies according to the frequency variation signal.

In the above referenced embodiments the pulse width modulated switch or regulation circuit may comprise a monolithic device.

An object of an aspect of the present invention is directed to a pulse width modulated switch that has integrated soft start capabilities.

Another object of an aspect of the present invention is directed toward a pulse width modulated switch that has integrated frequency variation capabilities.

Yet another object of an aspect of the present invention is directed toward a pulse width modulated switch that has integrated frequency variation capabilities and integrated soft start capabilities.

A further object of an aspect of the present invention is directed toward a low cost regulated power supply that has both soft start and frequency variation capabilities.

20 This and other objects and aspects of the present inventions are taught, depicted and described in the drawings and the description of the invention contained herein.

09880774-051898

7 8

Express Mail No. EM563810389US
Docket No. 233/248
May 12, 1998

FCS0000354

233/248
PATENT

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a known power supply utilizing a pulse width modulated switch, and external soft start, and frequency jitter functionality.

Fig. 2 is a presently preferred power supply utilizing an pulse width modulated switch according to the present invention.

Fig. 3 is a presently preferred pulse width modulated switch according to the present invention.

Fig. 4 is a timing diagram of the soft start operation of the presently preferred pulse width modulated switch according to the present invention.

Fig. 5 is a timing diagram of the frequency jitter operation of the presently preferred pulse width modulated switch according to the present invention.

Fig. 6 is an alternate presently preferred pulse width modulated switch according to the present invention.

Fig. 7 is a timing diagram of the operation of the alternate presently preferred pulse width modulated switch of Fig. 6 according to the present invention.

Fig. 8 is a presently preferred power supply utilizing a regulation circuit according to the present invention.

Fig. 9 is a presently preferred regulation circuit according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Fig. 2, EMI filter 200 is coupled to an AC mains voltage 205. The AC mains voltage 205 is rectified by rectifier 210. The rectified voltage 215 is provided to power supply capacitor 220 which provides a substantially DC voltage 225. The substantially DC

Express Mail No. EM563810388US
Docket No: 233/248
May 18, 1998

FCS0000355

233/248
PATENT

voltage 225 is provided to the primary winding 230 of transformer 235 which stores the energy provided to the primary winding 230. When the primary winding 230 is no longer receiving energy, energy is delivered by the transformer 235 to the secondary winding 240. The voltage induced across the secondary winding 240 is rectified by rectifier 245 and then transformed into
5 secondary substantially DC voltage 265 by secondary capacitor 260 and provided to the power supply output 267.

Energy is no longer provided to the primary winding 230 when the pulse width modulated switch 262, which is coupled to the primary winding 230, ceases conduction. Pulse width modulated switch 262 is a switch that is controlled by a pulse width modulated signal. Pulse width modulated switch 262 conducts and ceases conduction according to a duty cycle, that is in part determined by feedback from the power supply output 267. Pulse width modulated switch 262 is a switch that operates according to pulse width modulated control. Feedback to the pulse width modulated switch 262 is accomplished by utilization of feedback circuit 270, which is presently preferred to comprise a zener diode 275 in series with a resistor 280 and optocoupler 285. Optocoupler 285 provides a feedback current 290 to feedback terminal 295 of pulse width modulated switch 262. The feedback current is utilized to vary the duty cycle of a switch coupled between the first terminal 300 and second terminal 305 and thus regulate the output voltage, current or power of the power supply.

Although, it is presently preferred that the output voltage is utilized for feedback, the
20 present invention is also capable of utilizing either the current or power at the power supply output 267 without departing from the spirit and scope of the present invention.

A portion of the current supplied at the feedback terminal 295 is utilized to supply bias power for operation of the pulse width modulated switch 262. The remainder of the current

233/248
PATENT

input at the feedback terminal 295 is utilized to control the duty cycle of the pulse width modulated switch 262, with the duty cycle being inversely proportional to the feedback current.

A bias winding 310 is utilized to bias optocoupler 285 so that a feedback current can flow when light emitting diode 315 of optocoupler 285 conducts. The power supplied by the bias winding 310 is also used to charge pulse width modulation capacitor 330, the energy from which is utilized to power the pulse width modulated switch 262.

Overvoltage protection circuit 335 is utilized to prevent overvoltages from propagating through to the transformer 235.

Pulse width modulated switch 262 is supplied power during start up of the power supply by current flowing into the first terminal 300. An embodiment of one type of apparatus and method for designing a configuration for providing power to pulse width modulated switch through first terminal 300 is disclosed in commonly owned U.S. Patent No. 5,014,178 which is incorporated herein by reference in its entirety.

The drain terminal 300, source terminal 305 and feedback terminal 295 are the electrical input and/or output points of the pulse width modulated switch 262. They need not be part of a monolithic device or integrated circuit, unless the pulse width modulated switch 262 is implemented utilizing a monolithic device or integrated circuit.

Pulse width modulated switch 262 also may have soft start capabilities. When the device to which the power supply is coupled is switched on, a power up signal is generated within the internal circuitry of pulse width modulated switch 262. The power up signal is used to trigger soft start circuitry that reduces the duty cycle of the switch that operates within the pulse width modulated switch 262 for a predetermined period of time, which is presently preferred to be ten

233/248
PATENT

(10) milliseconds. Once soft start operation is completed, pulse width modulated switch 262 operates according to its regular duty cycle.

Alternatively, or in addition to soft start functionality, pulse width modulated switch 262 may also have frequency jitter functionality. That is, the switching frequency of the pulse width modulated switch 262 varies according to an internal frequency variation signal. This has an advantage over the frequency jitter operation of Fig. 1 in that the frequency range of the presently preferred pulse width modulated switch 262 is known and fixed, and is not subject to the line voltage or load magnitude variations. At low powers, those less than approximately ten (10) watts, the common mode choke which is often utilized as part of the EMI filter 120 can be replaced with inductors or resistors.

As can be seen when comparing the power supply of Fig. 1 to that of Fig. 2 the number of components utilized is reduced. This reduces the overall cost of the power supply as well as reducing its size.

Referring to Fig. 3, frequency variation signal 400 is utilized by the pulse width modulated switch 262 to vary its switching frequency within a frequency range. The frequency variation signal 400 is provided by frequency variation circuit 405, which preferably comprises an oscillator that operates at a lower frequency than main oscillator 465. The frequency variation signal 400, is presently preferred to be a triangular waveform that preferably oscillates between four point five (4.5) volts and one point five (1.5) volts. Although the presently preferred frequency variation signal 400 is a triangular waveform, alternate frequency variation signals such as ramp signals, counter output signals or other signals that vary in magnitude during a fixed period of time may be utilized as the frequency variation signal.

233/248
PATENT

The frequency variation signal 400 is provided to soft start circuit 410. During operation soft start circuit 410 is also provided with pulse width modulation frequency signal 415 and power up signal 420. Soft start enable signal 421 goes high at power up and remains high until oscillator signal 400 reaches its peak value for the first time. Soft start circuit 410 will provide a signal to or-gate 425 to reset latch 430 thereby deactivating conduction by the switch 435, which is presently preferred to be a MOSFET. Soft start circuit 410 will instruct switch 435 to cease conduction when the soft start enable signal 421 is provided and the magnitude of the frequency variation signal 400 is less than the magnitude of pulse width modulation signal 415. In other words, start up circuit 410 will allow the switch 435 to conduct as long as soft start enable signal is high and the magnitude of the pulse width modulation signal 415 is below the magnitude of frequency variation signal 400 as depicted in Fig. 4. In this way, the inrush current at startup will be limited for all cycles of operation, including the first cycle. By limiting the inrush current during all cycles of startup operation, the maximum current through each of the components of the power supply is reduced and the maximum current rating of each component can be decreased. The reduction in the ratings of the components reduces the cost of the power supply. Soft start signal 440 will no longer be provided by the frequency variation circuit 405 when the frequency variation signal 400 reaches its peak magnitude.

Operation of soft start circuit 410 will now be explained. Soft start circuit 410 comprises a soft start latch 450 that at its set input receives the power up signal 420 and its reset input receives the soft start signal 440. Soft start enable signal 421 is provided to one input of soft start and-gate 455 while the other input of soft start and-gate 455 is provided with an output from soft start comparator 460. The output of soft start comparator 460 will be high when the

233/248
PATENT

magnitude of frequency variation signal 400 is less than the magnitude of pulse width modulation oscillation signal 415.

The pulse width modulated switch 262 depicted in Fig. 3 also has frequency jitter functionality to help reduce the EMI generated by the power supply and pulse width modulated switch 262. Operation of the frequency jitter functionality will now be explained. Main oscillator 465 has a current source 470 that is mirrored by mirror current source 475. Main oscillator drive current 615 is provided to the current source input 485 of PWM oscillator 480. The magnitude of the current input into current source input 485 of PWM oscillator 480 determines the frequency of the pulse width modulation oscillation signal 415 which is provided by PWM oscillator 480. In order to vary the frequency of pulse width modulation oscillation signal 415, an additional current source 495 is provided within main oscillator 465. The additional current source 495 is mirrored by additional current source mirror 500. The current provided by additional current source 495 is varied as follows. Frequency variation signal 400 is provided to the gate of main oscillator transistor 505. As the magnitude of frequency variation signal 400 increases so does the voltage at the source of main oscillator transistor 505, due to the increasing voltage at the gate of main oscillation transistor and the relatively constant voltage drop between the gate and source of the main oscillation transistor 505. As the voltage at the source of main oscillation transistor 505 increases so does the current flowing through the main oscillation resistor 510. The current flowing through main oscillation resistor 510 is the same as the current flowing through additional current source 495 which is mirrored by additional current source mirror 500. Since, the presently preferred frequency variation signal 400 is a triangular waveform having a fixed period, the magnitude of the current input by additional current source mirror 500 will vary linearly with the magnitude of the rising and falling edges of the frequency

233/248
PATENT

variation signal 400. If the frequency variation signal 400 is a ramp signal, the frequency would linearly rise to a peak and then immediately fall to its lowest value. In this way, the current provided to current source input 485 of PWM oscillator 480 is varied in a known fixed range that allows for easy and accurate frequency spread of the high frequency current generated by the pulse width modulated switch. Further, the variance of the frequency is determined by the magnitude of the current provided by additional current source mirror 500, which is in turn a function of the resistance of main oscillation resistor 510.

Frequency variation circuit 405 includes a current source 525 that produces a fixed magnitude current 530 that determines the magnitude of the frequency of the frequency variation signal 400. Although, the presently preferred current 530 has a fixed magnitude, the frequency variation signal can be generated utilizing a variable magnitude current, if a variable current is generated the frequency spread would not be fixed in time but would vary with the magnitude of current 530. The fixed magnitude current 530 is fed into first transistor 535, mirrored by second transistor 540 and fed into third transistor 545. The frequency variation signal 400 is generated by the charging and discharging of frequency variation circuit capacitor 550. Frequency variation circuit capacitor 550 is presently preferred to have a relatively low capacitance, which allows for integration into a monolithic chip in one embodiment of the pulse width modulated switch 262. The frequency variation signal 400 is provided to upper limit comparator 555 and lower limit comparator 560. The output of upper limit comparator 555 will be high when the magnitude of the frequency variation signal 400 exceeds the upper threshold voltage 552 which is presently preferred to be four point five (4.5) volts. The output of lower limit comparator 560 will be high when the magnitude of frequency variation signal 400 exceeds lower threshold voltage 557 which is presently preferred to be one point five volts (1.5) volts. The output of

233/248
PATENT

upper limit comparator 555 is provided to the frequency variation circuit inverter 565 the output of which is provided to the reset input of frequency variation circuit latch 570. The set input of frequency variation circuit latch 570 receives the output of lower limit comparator 560. In operation, the output of lower limit comparator 560 will be maintained high for the majority of each cycle of frequency variation signal 400 because the magnitude of frequency variation signal will be maintained between upper threshold 552, 4.5 volts, and the lower threshold 557, 1.5 volts. The output of upper limit comparator 555 will be low until the magnitude of frequency variation signal 400 exceeds upper level threshold 552. This means that the reset input will receive a high signal until the magnitude of the frequency variation signal 400 rises above the upper threshold signal 552.

09280774.051898

The charge signal 575 output by frequency variation circuit latch 570 will be high until the frequency variation signal 400 exceeds the upper threshold limit signal 552. When the charge signal 575 is high, transistors 585 and 595 are turned off. By turning off transistors 585 and 595 current can flow into frequency variation circuit capacitor 550, which steadily charges frequency variation circuit capacitor 550 and increases the magnitude of frequency variation signal 400. The current that flows into frequency variation circuit capacitor 550 is derived from current source 525 because the current through transistor 590 is mirrored from transistor 580, which is mirrored from transistor 535.

During power up, when power-up signal 420 is low, the output of inverter 605 is high which turns on transistor 600 causing frequency variation signal 400 to go low. The frequency variation signal 400 is presently preferred to start from its lowest level to perform the soft start function during its first cycle of operation.

233/248
PATENT

Steady-state operation of the pulse width modulated switch 262, i.e. non start up operation, will now be described. PWM oscillator 480 provides pulse width modulation oscillation signal 415 to pulse width modulation comparator 609, the output of which will be high when the magnitude of pulse width modulation signal 415 is greater than the magnitude of a feedback signal 296 which is a function of the input provided at feedback terminal 295. When the output of pulse width modulation comparator 609 is high or-gate 425 is triggered to go high, which in turn resets pulse width modulation latch 430, removing the on signal from the control input switch 435, thereby turning off switch 435. Pulse width modulation latch 430 is set by clock signal 603, which is provided at the beginning of each cycle of pulse width modulation oscillator 480. Drive circuit 615, which is presently preferred to be an and-gate, receives the output of pulse width modulation latch 430, power up signal 420, and maximum duty cycle signal 607. As long as each one of the signals is high, drive signal 610 is provided to the gate of MOSFET 435, which is coupled between first terminal 300 and second terminal 305 of the pulse width modulated switch 262. When any of the output of pulse width modulation latch 430, power up signal 420, or maximum duty cycle signal 607 goes low drive signal 610 is no longer provided and switch 435 ceases conduction.

Referring to Fig. 4, frequency variation signal 400 preferably has a period, which is greater than that of pulse width modulated oscillation signal 415. The presently preferred period for frequency variation signal 400 is twenty (20) milliseconds, in order to allow for a smooth start up period which is sufficiently longer than the period of pulse width modulated signal 415 which is presently preferred to be ten (10) microseconds. Drive signal 610 will be provided only when the magnitude of pulse width modulated signal 415 is less than the magnitude of frequency

Express Mail No. EM563810388US
Docket No. 233/248
May 18, 1996

233/248
PATENT

variation signal 400. Further, frequency variation signal 400 will be preferably initiated starting from low voltage when power up signal 420 is provided.

Referring to Fig. 5, frequency variation signal 400 which is presently preferred to have a constant period is provided to the main oscillator 465. The magnitude of the pulse width modulator current 615 will approximately be the magnitude of frequency variation signal 400 divided by the resistance of resistor 510 plus the magnitude of the current produced by current source 470. In this way the pulse width modulator current 615 will vary with the magnitude of the frequency variation signal 400. The result is that the frequency of pulse width modulation signal is varied according to the magnitude of this current. It is presently preferred that the pulse width modulator current source produces a constant current having a magnitude of twelve point one (12.1) microamperes, and that frequency variation signal induced current 627 varies between zero (0) and eight hundred (800) nanoamperes. Thereby spreading the frequency of operation of the pulse width modulation oscillator 480 and reducing the average magnitude and the quasi-peak magnitude at all frequency levels of the EMI generated by the power supply.

Referring to Fig. 6, an alternate presently preferred pulse width modulated switch 262 includes all of the same components as described with respect to Fig. 3. In addition to these components, a second frequency variation circuit current source 660 and transistor 655 are added to the frequency variation circuit 405. Transistor 655 is activated only when the output of soft start latch 450 goes low. When transistor 655 is activated the current provided to the frequency variation circuit 405 increases as does the frequency of frequency variation signal 400.

However, transistor 655 will only be turned on when the output of soft start latch 450 goes low, i.e. when the magnitude of frequency variation signal 400 first reaches the upper threshold after power up. The period of frequency variation signal 400 will then increase after its first half

233/248
PATENT

cycle. This will decrease the period of the cycle during which the frequency is spread, without decreasing the frequency range. The benefit of the decreased cycle period will further decrease the quasi-peak levels of the EMI due to spending less time at each frequency level.

Referring to Fig. 7, operation of the frequency variation circuit 405 of Fig. 6 is depicted.

5 Frequency variation signal 405 will preferably have a period of ten (10) milliseconds for its first half cycle. After that, when the transistor 655 is turned on the period is preferably decreased to five (5) milliseconds. Pulse width modulated switch 262 is presently preferred to be a monolithic device.

Referring to Fig. 8, a power supply comprises a bridge rectifier 710 that rectifies an input AC mains voltage. Power supply capacitors 720 charge with the rectified AC mains voltage to maintain an input DC voltage 725. A presently preferred range for input DC voltage 725 is approximately one hundred (100) to four hundred (400) volts to allow for operation based upon worldwide AC mains voltages which range between eighty five (85) and two hundred sixty five (265) volts. The presently preferred power supply also includes harmonic filter components 910 which in combination with capacitors 720 reduce the harmonic current injected back into the power grid. Transformer 730 includes a primary winding 740 magnetically coupled to secondary winding 750. The secondary winding 750 is coupled to a diode 760 that is designed to prevent current flow in the secondary winding 750 when the regulation circuit 850 is conducting (on-state). A capacitor 770 is coupled to the diode 760 in order to maintain a continuous voltage on a load 780 which has a feedback circuit coupled to it. A presently preferred feedback circuit comprises an optocoupler 800 and zener diode 820. The output of optocoupler 800 is coupled to the feedback terminal 825 of regulation circuit 850. The presently preferred regulation circuit 850 switches on and off at a duty cycle that is constant at a given input DC voltage 725. A

233/248
PATENT

regulation circuit power supply bypass capacitor 860 is coupled to and supplies power to regulation circuit 850 when the regulation circuit 850 is in the on-state.

Operation of the power supply will now be described. An AC mains voltage is input through EMI filter 700 into bridge rectifier 710 which provides a rectified signal to power supply capacitors 720 that provide input DC voltage 725 to primary winding 740. Regulation circuit 850, which preferably operates at a constant frequency and about constant duty cycle at a given input DC voltage 725, allows current to flow through primary winding 740 during its on state of each switching cycle and acts as open circuit in its off state. When current flows through primary winding 740 transformer 730 is storing energy, when no current is flowing through primary winding 740 any energy stored in transformer 730 is delivered to secondary winding 750. Secondary winding 750 then provides the energy to capacitor 770. Capacitor 770 delivers power to the load 780. The voltage across the load 780 will vary depending on the amount of energy stored in the transformer 730 in each switching cycle which is in turn dependent on the length of time current is flowing through primary winding 740 in each switching cycle which is presently preferred to be constant at a given input DC voltage 725. The presently preferred regulation circuit 850 allows the voltage delivered to the load to be maintained at a constant level.

It is presently preferred that the sum of the voltage drop across optocoupler 800 and the reverse break down voltage of zener diode 820 is approximately equal to the desired threshold level. When the voltage across the load 780 reaches the threshold level, current begins to flow through the optocoupler 800 and zener diode 820 that in turn is used to disable the regulation circuit 850. Whenever regulation circuit 850 is in the off-state the regulation circuit power supply bypass capacitor 860 is charged to the operating supply voltage, which is presently

19 20

Express Mail No. EM5634103187US
Docket No: 233/248
May 18, 1998

FCS0000366

233/248
PATENT

preferred to be five point seven (5.7) volts by allowing a small current to flow from bypass terminal 865 to the regulation circuit power supply bypass capacitor 860. Regulation circuit power supply bypass capacitor 860 is used to supply power to operate regulation circuit 850 when it is in the on-state.

5 When the regulation circuit 850 is disabled, an open circuit condition is created in primary winding 740 and transformer 730 does not store energy. The energy stored in the transformer 730 from the last cycle of regulation circuit 850 is then delivered to secondary winding 750 which in turn supplies power to the load 780. Once the remaining energy in transformer 750 is delivered to the load 780 the voltage of the load 780 will decrease. When the voltage at the load 780 decreases below the threshold level, current ceases to flow through optocoupler 800 and regulation circuit 850 resumes operation either instantaneously or nearly instantaneously.

The presently preferred regulation circuit 850 has a current limit feature. The current limit turns off the regulation circuit 850, when the current flowing through the regulation circuit 850 rises above a current threshold level. In this way regulation circuit 850 can react quickly to changes such as AC ripple that occur in the rectified AC mains voltage, and prevents the propagation of the voltage changes to the load. The current limit increases the responsiveness of the regulation circuit to input voltage changes and delivers constant power output independent for the AC mains input voltage.

20 Although the presently preferred power supply of Fig. 8 utilizes current mode regulation and a feedback circuit that includes an optocoupler and zener diode, the present invention is not to be construed as to be limited to such a feedback method or circuit. Either current or voltage mode regulation may be utilized by the present invention without departing from the spirit and

20 21

Express Mail No. EN563410348US
Docket No. 233/248
May 14, 1998

FCS0000367

233/248
PATENT

scope of the present invention so long as a signal indicative of the power supplied to the load is supplied to the feedback terminal 825 of the regulation circuit 850. Additionally, although the presently preferred power supplies both utilize an optocoupler and zener diode as part of feedback circuits other feedback circuits may be utilized by the present invention without
5 departing from the spirit and scope of the present invention.

Regulation circuit 850 also may have integrated soft start capabilities. When the device to which the power supply is coupled is switched on, a power up signal is generated within the internal circuitry of regulation circuit 850. A power up signal is used to trigger soft start circuitry that reduces the duty cycle of the switch that operates within the pulse width modulated switch 262 for a predetermined period of time, which is presently preferred to be ten (10) milliseconds. Once soft start operation is completed, regulation circuit 850 operates according to its regular duty cycle.

Alternatively, or in addition to soft start functionality, regulation circuit 850 may also have frequency jitter functionality. That is, the switching frequency of the regulation circuit 850 varies according to an internal frequency variation signal. This has an advantage over the frequency jitter operation of Fig. 1 in that the frequency range of the presently regulation circuit 850 is known and fixed, and is not subject to the line voltage or load magnitude variations.

Referring to Fig. 9, frequency variation circuit 405 and main oscillator 465 function as described with respect to Fig. 3. In operation it is the variance of the high and low states of
20 maximum duty cycle signal 607 that generates the frequency jitter functionality of the regulation circuit 850. A presently preferred regulation circuit 850 and its steady-state operation is depicted and described in copending patent application serial No. 09/032,520 which is hereby incorporated by reference in its entirety.

21 22

Express Mail No. EMS63810388US
Docket No. 233/248
May 18, 1998

FCS0000368

233/248
PATENT

The regulation circuit of Fig. 9 can be modified to include a second current source to further increase the period of main oscillation signal 415 which achieves the same result and function as described with respect of Figs. 6 and 7.

The soft start functionality of the presently preferred regulation circuit 850 of Fig. 9, will shorten the on-time of switch 435 to less than the time of the maximum duty cycle signal 607 as long as the soft start enable signal 421 is provided and the magnitude of frequency variation signal 400 is less than the magnitude of main oscillation signal 415.

The presently preferred regulation circuit 850 preferably comprises a monolithic device.

While the embodiments, applications and advantages of the present invention have been depicted and described, there are many more embodiments, applications and advantages possible without deviating from the spirit of the inventive concepts described herein. Thus, the inventions are not to be restricted to the preferred embodiments, specification or drawings. The protection to be afforded this patent should therefore only be restricted in accordance with the spirit and intended scope of the following claims.

09080774-051898

22 23

Express Mail No. EM563810388US
Docket No. 233/248
May 11, 1998

FCS0000369

233/248
PATENT

CLAIMS

What Is Claimed Is:

1. A pulse width modulated switch comprising:

a first terminal;

a second terminal;

a switch comprising a control input, said switch allowing a signal to be transmitted between said first terminal and said second terminal according to a drive signal provided at said control input;

a frequency variation circuit that provides a frequency variation signal;

an oscillator that provides an oscillation signal having a frequency range, said frequency of said oscillation signal varying within said frequency range according to said frequency variation signal, said oscillator further providing a maximum duty cycle signal comprising a first state and a second state; and

a drive circuit that provides said drive signal when said maximum duty cycle signal is in said first state and a magnitude of said oscillation signal is below a variable threshold level.

2. The pulse width modulated switch of claim 1 wherein said first terminal, said second terminal, said switch, said oscillator, said frequency variation circuit and said drive circuit comprise a monolithic device.

3. The pulse width modulated switch of claim 1 wherein said frequency variation circuit comprises an additional oscillator that provides said frequency variation signal to said

23 24

Excerpt Mail No. EM56381038816
Docket No: 233/248
May 18, 1998

FCS0000370

233/248
PATENT

oscillator, said frequency of said oscillation signal varying within said frequency range according to said frequency variation signal.

4. The pulse width modulated switch of claim 1 further comprising a soft start
5 circuit that provides a signal instructing said drive circuit to discontinue said drive signal when a
magnitude of said oscillation signal is greater than a magnitude of said frequency variation
signal.

5. The pulse width modulated switch of claim 4 wherein said additional oscillator
10 provides a soft start signal, and wherein said soft start circuit ceases operation when said soft
start signal is removed.

6. The pulse width modulated circuit of claim 5 wherein said additional oscillator
further comprises
15 a comparator that provides a comparator signal when a magnitude of a reference signal is
greater than or equal to a magnitude of said frequency variation signal, and
an inverter that receives said comparator signal and provides said soft start signal.

7. The pulse width modulated switch of claim 1 wherein said frequency of said
20 oscillation signal varies within said frequency range with a magnitude of said frequency
variation signal.

24

25

Express Mail No. EHC563810388US
Docket No: 233/248
May 18, 1998

FCS0000371

233/248
PATENT

8. The pulse width modulated switch of claim 1 wherein said oscillator comprises a
an input that receives said frequency variation signal and a current source, wherein said
frequency of said oscillation signal is a function of a sum of a magnitude of a current provided
by said current source and a magnitude of said frequency variation signal.

9. The pulse width modulated switch of claim 1 further comprising
a rectifier comprising a rectifier input and a rectifier output, said rectifier input receiving
an AC mains signal and said rectifier output providing a rectified signal;
a power supply capacitor that receives said rectified signal and provides a substantially
DC signal;
a first winding comprising a first terminal and a second terminal, said first winding
receiving said substantially DC signal, said second terminal of said first winding coupled to said
first terminal of said pulse width modulated switch; and
a second winding magnetically coupled to said first winding, said first winding capable of
being coupled to a load.

10. The pulse width modulated switch of claim 1 wherein said variable threshold
level is a function of a feedback signal received at a feedback terminal of said pulse width
modulated switch.

11. A pulse width modulated switch comprising
a first terminal;
a second terminal;

Express Mail No. E94563810380US
Docket No: 233/248
May 18, 1998

FCS0000372

233/248
PATENT

a switch comprising a control input, the switch allowing a signal to be transmitted between said first terminal and said second terminal according to a drive signal provided at said control input;

an oscillator that provides a maximum duty cycle signal comprising an on-state and an off-state;

a drive circuit that provides said drive signal according to said maximum duty cycle signal; and

a soft start circuit that provides a signal instructing said drive circuit to disable said drive signal during at least a portion of said on-state of said maximum duty cycle.

12. The pulse width modulated switch of claim 11 wherein said a first terminal, said second terminal, said switch, said oscillator, said drive circuit and said soft start circuit comprise a monolithic device.

13. The pulse width modulated switch of claim 11 further comprising an additional oscillator that provides a soft start signal to said soft start circuit, and wherein when said soft start signal is removed said soft start circuit ceasing operation.

14. The pulse width modulated circuit of claim 13 wherein said additional oscillator further comprises

a comparator that provides a comparator signal when a magnitude of a reference signal is greater than or equal to a magnitude of said frequency variation oscillation signal, and

an inverter that receives said comparator signal and provides said soft start signal.

233/248
PATENT

15. The pulse width modulated switch of claim 11 further comprising a frequency variation circuit that provides a frequency variation signal, wherein said oscillator provides an oscillation signal and wherein said soft start circuit provides said signal instructing said drive circuit to disable said drive signal when a magnitude of said oscillation signal is greater than a magnitude of said frequency variation signal.

16. The pulse width modulated switch of claim 15 wherein said oscillator comprises an input that receives said frequency signal and said oscillation signal comprises a frequency range, and wherein said frequency of said oscillation signal varies within said frequency range according to a magnitude of said frequency variation signal.

17. The pulse width modulated switch of claim 16 wherein said oscillator further comprises a current source, wherein said frequency of said oscillation signal is a function of a sum of a magnitude of a current provided by said current source and said magnitude of said frequency variation signal.

18. The pulse width modulated switch of claim 11 further comprising a rectifier comprising a rectifier input and a rectifier output, said rectifier input receiving an AC mains signal and said rectifier output providing a rectified signal;

a power supply capacitor that receives said rectified signal;

a first winding comprising a first terminal and a second terminal, said first winding receiving a substantially DC signal from said power supply capacitor, said second terminal of said first winding coupled to said first terminal of said pulse width modulated switch; and

233/248
PATENT

~~X~~ a second winding magnetically coupled to said first winding, said first winding capable of being coupled to a load.

19. A regulation circuit comprising
5 a first terminal;
a second terminal;
a switch comprising a control input, said switch allowing a signal to be transmitted between said first terminal and said second terminal according to a drive signal provided at said control input;
a drive circuit that provides said drive signal for a maximum time period of a cycle; and
a soft start circuit that provides a signal instructing said drive circuit to disable said drive signal during at least a portion of said maximum time period.

20. The regulation circuit of claim 19 further comprising an oscillator that provides a maximum duty cycle signal to said drive circuit, said maximum duty cycle signal comprising an on-state for said maximum time period.

21. The regulation circuit of claim 20 further comprising a frequency variation circuit that provides a frequency variation signal, wherein said oscillator provides an oscillation signal and wherein said soft start circuit provides said signal instructing said drive circuit to disable said drive signal when a magnitude of said oscillation signal is greater than a magnitude of said frequency variation signal.

Express Mail No. EM563810388US
Docket No. 233/248
May 18, 1996

233/248
PATENT

22. The regulation circuit of claim 19 further comprising an additional oscillator that provides a soft start signal to said soft start circuit, and wherein when said soft start signal is removed said soft start circuit ceasing operation.

5 23. The regulation circuit of claim 22 wherein said additional oscillator further comprises

a comparator that provides a comparator signal when a magnitude of a reference signal is greater than or equal to a magnitude of said additional oscillation signal, and

an inverter that receives said comparator signal and provides said soft start signal

24. The regulation circuit of claim 19 further comprising a frequency variation circuit that provides a frequency variation signal and wherein said maximum time period varies according to a magnitude of said frequency variation signal.

25. The regulation circuit of claim 19 further comprising a feedback terminal and wherein when a signal is received at said feedback terminal said drive signal is discontinued for at least one cycle.

20 26. The regulation circuit of claim 19 wherein said first terminal, said second terminal, said oscillator and said soft start circuit comprise a monolithic device.

09880774.051808

Express Mail No. EM563810100105
Docket No: 233/248
May 18, 1998

233/248
PATENT

27. The regulation circuit of claim 26 further comprising a current limit circuit that provides a signal instructing said drive circuit to discontinue said drive signal when a current received at said first terminal of said regulation circuit is above a threshold level.

5 28. The regulation circuit of claim 19 further comprising
a rectifier comprising a rectifier input and a rectifier output, said rectifier input receiving
an AC mains signal and said rectifier output providing a rectified signal;
a power supply capacitor that receives said rectified signal;
a first winding comprising a first terminal and a second terminal, said first winding
receiving a substantially DC signal from said power supply capacitor, said second terminal of
said first winding coupled to said first terminal of said regulation circuit; and
a second winding magnetically coupled to said first winding, said first winding capable of
being coupled to a load.

09880774-051808
B8875D-470886D

Cal
A37

29. A regulation circuit comprising:
a first terminal;
a second terminal;
a switch comprising a control input, said switch allowing a signal to be transmitted
between said first terminal and said second terminal according to a drive signal provided at said
20 control input; and
a frequency variation circuit that provides a frequency variation signal;
a drive circuit that provides said drive signal for a maximum time period of a time
duration cycle;

Express Mail No. 884563810388US
Docket No: 233/248
May 18, 1998

233/248
PATENT

wherein said time duration of said cycle varies according to said frequency variation signal

- 12
20. The regulation circuit of claim 11 wherein said frequency variation circuit
5 comprises an oscillator that provides said frequency variation signal.

31. The regulation circuit of claim 29 further comprising a soft start circuit that provides a signal instructing said drive circuit to discontinue said drive according to a magnitude of said frequency variation signal.

14
32. The regulation circuit of claim 31 further wherein said frequency variation circuit provides a soft start signal, and wherein said soft start circuit ceases operation when said soft start signal is removed.

15
33. The regulation circuit of claim 32 wherein said frequency variation circuit further comprises

a comparator that provides a comparator signal when a magnitude of a reference signal is greater than or equal to a magnitude of said frequency variation signal, and

an inverter that receives said comparator signal and provides said soft start signal.

20

16
34. The regulation circuit of claim 11 wherein said first terminal, said second terminal, said switch, said frequency variation circuit, and said drive circuit comprise a monolithic device.

31 27

Express Mail No. E4563816388US
Docket No: 233/248
May 18, 1998

FCS0000378

233/248
PATENT

35. The regulation circuit of claim 29 further comprising
 a rectifier comprising a rectifier input and a rectifier output, said rectifier input receiving
 an AC mains signal and said rectifier output providing a rectified signal;
 a power supply capacitor that receives said rectified signal and provides a substantially
 DC signal;
 a first winding comprising a first terminal and a second terminal, said first winding
 receiving said substantially DC signal, said second terminal of said first winding coupled to said
 first terminal of said regulation circuit; and
 a second winding magnetically coupled to said first winding, said first winding capable of
 being coupled to a load.


36. The regulation circuit of claim 29 further comprising a current limit circuit that
 provides a signal instructing said drive circuit to discontinue said drive signal when a current
 received at said first terminal of said regulation circuit is above a threshold level.

37. The regulation circuit of claim 29 further comprising a feedback terminal and
 wherein when a signal is received at said feedback terminal said drive signal is discontinued for
 at least one cycle.

Express Mail No. E84563818388US
Docket No. 233/248
May 18, 1998

868150-4208060

FIG. 1




233/248
PATENT

Express Mail No. EM563810388US
Docket No: 233/248
May 14, 1998

Fig 9


868T50*42408060

FIG. 2




233/248
PATENT

Express Mail No. EM561810388125
Docket No. 233/248
May 18, 1998

233/248
PATENT

Express Mail No. EM563810388US
Docket No. 231/248
May 18, 1994



233/248
PATENT

FIG. 4

Express Mail No. EM563810388US
Docket No. 233/248
May 18, 1996

233/248
PATENT

868150*42408060






FIG. 5

Express Mail No. 884563810388105
Docket No: 233/248
May 18, 1998

233/248
PATENT



868T50-n4408060



39

233/248
PATENT

FIG. 7

Express Mail No. E84563810388US
Docket No: 233/248
May 18, 1998

FCS0000386

233/248
PATENT

888750-4208060




FIG. 8

Express Mail No. E4561810387LS
Doclet No. 233/248
May 18, 1998

233/248
PATENT

868T50-47408060




FIG. 9

Express Mail No. EM56381038825
Docket No. 233/248
May 18, 1998

233/248
PATENT

ABSTRACT

A pulse width modulated switch comprises a first terminal, a second terminal, and a switch that allows a signal to be transmitted between the first terminal and the second terminal according to a drive signal provided at a control input. The pulse width modulated switch also comprises a frequency variation circuit that provides a frequency variation signal and an oscillator that provides an oscillation signal having a frequency of that varies within a frequency range according to the frequency variation signal. The oscillator further provides a maximum duty cycle signal comprising a first state and a second state. The pulse width modulated switch further comprises a drive circuit that provides the drive signal when the maximum duty cycle signal is in the first state and a magnitude of the oscillation signal is below a variable threshold level.

09980774.051898

**DECLARATION
AND POWER OF ATTORNEY
Utility Application**

LYON & LYON LLP

233/248

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **"OFF-LINE CONVERTER WITH INTEGRATED SOFTSTART AND FREQUENCY HITTER"**, the specification of which

Check One

- ☒ is attached hereto.
☐ was filed on _____ as
 Application Serial No. _____
 and was amended on _____

(If applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a). I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Application Number	Country	Date of Filing	Priority Claimed	
			Yes%	No%

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

Application Number	Date of Filing	Status—Patented, Pending or Abandoned

POWER OF ATTORNEY: As a named inventor, I hereby appoint as my attorneys, with full power of substitution and revocation, to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Roland N. Smoot, Reg. No. 18,718; Conrad R. Solum, Jr., Reg. No. 20,467; James W. Geriak, Reg. No. 20,233; Robert M. Taylor, Jr., Reg. No. 19,848; Samuel B. Stone, Reg. No. 19,287; Douglas E. Olson, Reg. No. 22,798; Robert E. Lyon, Reg. No. 24,171; Robert C. Weiss, Reg. No. 24,939; Richard E. Lyon, Jr., Reg. No. 26,300; John D. McConaghy, Reg. No. 26,773; William C. Steffin, Reg. No. 26,811; Coe A. Bloomberg, Reg. No. 26,605; J. Donald McCarthy, Reg. No. 25,119; John M. Benassi, Reg. No. 27,483; James H. Shalek, Reg. No. 29,749; Allan W. Jansen, Reg. No. 29,395; Robert W. Dickerson, Reg. No. 29,914; Roy L. Anderson, Reg. No. 30,240; David B. Murphy, Reg. No. 31,125; James C. Brooks, Reg. No. 29,898; Jeffrey M. Olson, Reg. No. 30,790; Steven D. Henninger, Reg. No. 30,755; Jerrold B. Reilly, Reg. No. 32,293; Paul H. Meier, Reg. No. 32,274; John A. Rafter, Jr., Reg. No. 31,653; Kenneth H. Ohrliner, Reg. No. 31,646; Mary S. Consalvi, Reg. No. 32,212; Lois M. Kwasigroch, Reg. No. 35,579; Lawrence R. LaPorte, Reg. No. 38,948; Robert C. Laursen, Reg. No. 34,206; Carol A. Schneider, Reg. No. 34,923; Hope E. Meville, Reg. No. 34,874; Michael J. Wise, Reg. No. 34,047; Richard J. Warburg, Reg. No. 32,327; David T. Burse, Reg. No. 37,104; Jeffrey A. Miller, Reg. No. 35,287; Bernard F. Rose, Reg. No. P-42,112; Michael J. Bolan, Reg. No. P-42,339; Lynn Y. McKernan, Reg. No. P-41,986; and Dmitry R. Milikovsky, Reg. No. P-41,999.

DPOA.Uti

Update 4/97

FCS0000390

APPLICABLE STATUTES & RULES

37 CFR 1.56 DUTY TO DISCLOSE INFORMATION MATERIAL TO PATENTABILITY

(a) A patent by its very nature is afforded with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is cancelled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is cancelled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by ss 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) prior art cited in search reports of a foreign patent office in a counterpart application, and
 - (2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.
- (b) Under this section information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and
- (1) it establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim;
- or
- (2) it refutes, or is inconsistent with, a position the applicant takes in:
 - (i) Opposing an argument of unpatentability relied on by the Office, or
 - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

- (c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:
- (1) Each inventor named in the application;
 - (2) Each attorney or agent who prepares or prosecutes the application; and
 - (3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.
- (d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.

35 U.S.C. 102. CONDITIONS FOR PATENTABILITY; NOVELTY AND LOSS OF RIGHT TO PATENT

- A person shall be entitled to a patent unless—
- (a) the invention was known or used by others in this country, or patented or described in a printed publication in this or a foreign country, before the invention thereof by the applicant for patent, or
 - (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of the application for patent in the United States, or
 - (c) he has abandoned the invention, or
 - (d) the invention was first patented or caused to be patented, or was the subject of an inventor's certificate, by the applicant or his legal representatives or assigns, in a foreign country prior to the date of the application for patent in this country on an application for patent or inventor's certificate filed more than twelve months before the filing of the application in the United States, or
 - (e) the invention was described in a patent granted on an application for patent by another filed in the United States before the invention thereof by the applicant for patent, or on an international application by another who has fulfilled the requirements of paragraphs (1), (2), and (4) of section 371(c) of this title before the invention thereof by the applicant for patent, or
 - (f) he did not himself invent the subject matter sought to be patented, or
 - (g) before the applicant's invention thereof the invention was made in this country by another who had not abandoned, suppressed, or concealed it. In determining priority of invention there shall be considered not only the respective dates of conception and reduction to practice of the invention, but also the reasonable diligence of one who was first to conceive and last to reduce to practice, from a time prior to conception by the other.

35 U.S.C. 103. CONDITIONS FOR PATENTABILITY; NON-OBVIOUS SUBJECT MATTER

A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Subject matter developed by another person, which qualifies as prior art only under subsection (b) or (g) of section 102 of this title, shall not preclude patentability under this section where the subject matter and the claimed invention were, at the time the invention was made, owned by the same person or subject to an obligation of assignment to the same person.

35 U.S.C. 119. BENEFIT OF EARLIER FILING DATE IN FOREIGN COUNTRY; RIGHT OF PRIORITY (Applicable Portion)

An application for patent for an invention filed in this country by any person who has, or whose legal representatives or assigns have, previously regularly filed an application for a patent for the same invention in a foreign country which affords similar privileges in the case of applications filed in the United States or to citizens of the United States, shall have the same effect as the same application would have if filed in this country on the date on which the application for patent for the same invention was first filed in such foreign country, if the application in this country is filed within twelve months from the earliest date on which such foreign application was filed; but no patent shall be granted on any application for a patent for an invention which has been patented or described in a printed publication in any country more than one year before the date of the actual filing of the application in this country, or which had been in public use or on sale in this country more than one year prior to such filing.

35 U.S.C. 120. BENEFIT OF EARLIER FILING DATE IN THE UNITED STATES

An application for patent for an invention disclosed in the manner provided by the first paragraph of section 112 of this title in an application previously filed in the United States, or as provided by section 363 of this title, by the same invention shall have the same effect, as to such invention, as though filed on the date of the prior application, if filed before the patenting or abandonment of or termination of proceedings on the first application or on an application similarly entitled to the benefit of the filing date of the first application and if it contains or is amended to contain a specific reference to the earlier filed application.

35 U.S.C. 112. SPECIFICATION (Applicable Portion)

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make the use the same, and shall set forth the best mode contemplated by the inventor of carrying out his invention.

The specification shall conclude with one or more claims particularly pointing out and distinctive claiming the subject matter which the applicant regards as his invention.

11/04/01/01

Update: 4/97

FCS0000391